

ADELUCU-EOL

Alarmline II Digital EN -
Spare end-of-line unit



General

Replacement end-of-line unit for use with the AlarmLine II Digital EN Linear Heat Detection Controller and AlarmLine II Digital EN Linear Heat Detection Cable.

Functional testing

Internally the unit features 4 switches, which can be used to simulate a fire or fault on each of the zones. There are two push-buttons, one for each zone, which simulate a fire by connecting the two cable cores when the button is pressed. Similarly there are two switches, which under normal conditions connect the end-of-line resistor across the cable, for each zone. However when the switch is changed, this creates an open circuit which in turn raises a fault on the controller. Via these switches it is easy to functionally test the system.

Details

- Quickly simulate a fault condition
- Quickly simulate an alarm condition
- Supplied with 2 IP67 rated cable glands
- Secure, weatherproof enclosure
- RoHS Compliant, CE & EN54-28:2016 Certified



Australia & New Zealand

Phone: 1800 654 435

Email: cs@firesecurityproducts.zendesk.com

Web: www.kidde.com.au

Head Office

Building F, Unit 1, 3-29 Birnie Avenue

Lidcombe NSW 2141

Australia

©2025 Kidde. All rights reserved.

Technical specifications

Physical

| | |
|---------------------|-----------------------------|
| Physical dimensions | 94 x 94 x 57 mm (W x H x D) |
|---------------------|-----------------------------|

| | |
|-----------|-------------------|
| Terminals | 5 mm rising clamp |
|-----------|-------------------|

Environmental

| | |
|-----------------------|--------------|
| Operating temperature | -35 to +55°C |
|-----------------------|--------------|

| | |
|-----------|------|
| IP rating | IP66 |
|-----------|------|

Standards & regulation

| | |
|---------------|-------------|
| Certification | CE, EN54-28 |
|---------------|-------------|
