

Manual/Thermal Activation Stat-X® Fire Suppression Generators



Model	Part No.	Aerosol Mass	Weight	Length	Diameter	Discharge Time
30T	15300	30 grams	.3 kg. / .66 lb.	109 mm/ 4.30 inches	51 mm/ 2.00 inches	8 seconds
60T (long)	15311	60 grams	.49 kg. / 1.1 lbs.	155 mm/ 6.10 inches	51 mm/ 2.00 inches	8.5 seconds
100T	15410	100 grams	.827 kg. / 1.82 lbs.	152 mm/ 6.00 inches	76 mm/ 3.00 inches	11.5 seconds
250T	15510	250 grams	2.48 kgs. / 5.47 lbs.	168 mm/ 6.60 inches	127 mm/ 5.00 inches	12 Seconds
250MT	15511	250 grams	1.28 kgs / 2.83 lbs.	202 mm/ 7.95 inches	76 mm/ 3.00 inches	18 seconds
500T	15610	500 grams	3.43 kgs. / 7.56 lbs.	218 mm/ 8.60 inches	127 mm/ 5.00 inches	21 seconds
1000MT	15711	1000 grams	5.54 kgs. / 12.2 lbs.	333 mm/ 13.10 inches	127 mm/ 5.00 inches	25 seconds

Please note that the length dimensions and weights that are listed above for the Stat-X generators are based on the length of the generators with the thermal/manual heads installed on the generators.

For additional information on use of Stat-X systems, please contact your local distributor or Fireaway Inc.

Operation/Storage Parameters:

Temperature -0° C to +54° C (+32° F to 130° F)
Relative Humidity up to 98% at +35° C (+95° F)

Dangerous Goods Transportation Classification:

For transporting by public highway, rail, marine vessel or cargo aircraft only: Special Permit DOT-SP 20600 authorizes transport as Proper Shipping Name: UN3268 Safety Devices 9.
For shipment by air (cargo or passenger): International Air Transport Association (IATA) regulations authorize the Proper Shipping Name: UN0432 Articles pyrotechnic 1.4S

Shipping Limitations:

Ground: Placards required for any shipment of > 1001 lbs. as UN0432 1.4S
Max. Net Qty/Pkg- Cargo Air 100 kgs (220 lbs)
Max. Net Qty/Pkg- Passenger Air 25 kgs (55 lbs)

